

Industry Articulated Lights

GSL



● RAL 9006 /silver

TECHNISCHE DATEN

V	220-240
Hz	50-60
W	8 / 12 / 18 / 24
Lm	2000 / 4000
K	4000 / 5000
Lux	2100 / 3000 / 4100 / 4500 (50cm)
CRI	> 80 (typ. 83)
kg	2,85 / 3,1 / 3,3 / 3,5
RG	0

Material:	Naturally anodized aluminum
Joint type:	Spring-assisted articulated arm in the middle and base joints
Dimming:	Optional (nonDim/DIM 1-100%) 50,000
Service life:	hours
Warranty:	2 years
LED cover:	Microprismatic lens/plus additional high-tech diffuser film
Power connection:	2m PVC cable + Schuko plug
LED driver:	Tridonic
Color:	Silver
Light head dimension:	8W: 300 x 111 x 35.5 mm (LxWxH) 12W: 350 x 111 x 35.5 mm (LxWxH) 18W: 445 x 111 x 35.5 mm (LxWxH) 24W: 585 x 111 x 35.5 mm (LxWxH)



ITEM NUMBERS



4000 Kelvin

Length	Power	Dimmable	Item no.:
300mm	8 W	X	GSL8.840S
350mm	12 W	✓	GSL12.840sd
445mm	18 W	✓	GSL18.840sd
585mm	24 W	✓	GSL24.840sd



5000 Kelvin

Length	Power	Dimmable	Item no.:
300mm	8 W	X	GSL8.850S
350mm	12 W	✓	GSL12.850sd
445mm	18 W	✓	GSL18.850sd
585mm	24 W	✓	GSL24.850sd

HIGHLIGHTS

- ✓ Four lamp head widths – 300 mm, 350 mm, 445 mm, and 585 mm for different working areas
- ✓ Neutral white light (4000 K or 5000 K) with high color rendering (CRI > 80) and homogeneous, large-area light distribution
- ✓ Microprism lens with dual-function diffuser film – reversible for variable diffusion and optimal glare control
- ✓ 3D joint on the lamp head and sturdy metal frame for precise adjustability and durability
- ✓ Integrated LED converter in the luminaire arm – no external power supply required



ATTACHMENTS

For all variants



Screw-on flange (incl.)
SKU: 00595



Table clamp 0-44 mm
SKU: 00395



Table clamp 16-85 mm
SKU: 00495



Tabel base 10,5 kg
SKU: 31796



Wall angle
SKU: 00295

Zum Weiherlein 16
97509 Kolitzheim
Germany

Sales: +49(0)15128033591
info@rmd-leuchten.de
www.rmd-leuchten.de

