

Articulated Lamps

SPECIAL LINE 36W



SKU: 289.32.97sd-D4 (silver)

● RAL 9006 / silver




SKU: 289-32.90sd-D4 (black)

● RAL 9005 / black

TECHNICAL DATA


V	220-240
Hz	50-60
W	36
Lm	4464
K	5700
Lux	9000 (40cm)
CRI	> 95 (typ. 97)
kg	5,5
RG	0

Body:	natural-anodised aluminium
Articulation type:	Gas spring arm with 2 integrated gas springs (parallelogram)
Dimming:	Push-button (ON/OFF/DIM) / 1-100%
Lifetime:	50.000h
Warranty:	2 Years
LED Cover:	Microprismatic lens/plus additional high-tech diffuser film
Power connection:	2m PVC-Cable + Schuko plug
LED Driver:	Tridonic
Colour:	Silver / Black
Dimensions light head:	581 x 150 x 35,5 mm (LxWxH)



HIGHLIGHTS

- ✓ No colour location shifts when dimming the LEDs
- ✓ No UV and infrared components in the light spectrum (prevents e.g. premature hardening of plastics)
- ✓ No heat load in the direction of light emission - only slight heating of the luminaire head
- ✓ Extremely bright thanks to a three-row LED arrangement, large-area illumination – up to 9000 lx illuminance at a distance of 40 cm
- ✓ Parallelogram-guided articulated arm with integrated gas struts: infinitely easy to adjust without opening a locking screw, no uncontrolled sagging due to inadvertent misuse



ATTACHMENTS

SKU: 289.32.97sd-D4 (silver)



Screw-on flange (incl.)
SKU: 005.95



Table clamp 0-44 mm
SKU: 003.95



Table clamp 16-85 mm
SKU: 004.95



Tabel base 10,5 kg
SKU: 317.96



Wall angle
SKU: 002.95

SKU: 289-32.90sd-D4 (black)



Screw-on flange (incl.)
SKU: 005.90



Table clamp 0-44 mm
SKU: 003.90



Table clamp 16-85 mm
SKU: 004.90

OPTIONAL

Shortened lower arm for board mounting



Special Line (10cm shortened)

Silver-SKU: 289-36.96sd-D4
Black-SKU: 289-36.91sd-D4



Zum Weiherlein 16
97509 Kolitzheim
Germany

Sales: +49(0)15128033591
info@rmd-leuchten.de
www.rmd-leuchten.de

